



Installing MacBook Pro 15" Unibody Late 2008 and Early 2009 RAM

Tools used in this guide

- [Phillips #00 Screwdriver](#) (1)

Parts relevant to this guide

- [PC3-8500 2 GB RAM Chip](#) (1)
- [PC3-8500 1 GB RAM Chip](#) (1)

Accessing the RAM in this computer is straightforward and requires minimal disassembly.



Step 1 - Access Door

- With the case closed, place the Unibody top-side down on a flat surface.
- Depress the grooved side of the access door release latch enough to grab the free end. Lift the release latch until it is vertical.



Step 2

- The access door should now be raised enough to lift it up and out of the Unibody.




Step 3 - Battery

- Be sure the access door release latch is vertical before proceeding.
- Grab the translucent plastic tab and pull the battery up and out of the Unibody.
- If the latch is depressed it will lock the battery in place.




Step 4 - Lower Case

- Remove the following eight screws securing the lower case to the chassis:
 - One 5.4 mm Phillips screw.
 - Three 14 mm Phillips screws.
 - Four 3.5 mm Phillips screws.




Step 5

- Using both hands, lift and remove the lower case off the upper case.



Step 6 - RAM

- Release the tabs on each side of the chip by simultaneously pushing each tab away from the RAM.
- These tabs lock the chip in place and releasing them will cause the chip to "pop" up.



Step 7

- After the RAM chip has popped up, pull it straight out of its socket.
- Repeat this process if a second RAM chip is installed.



To reassemble your device, follow these instructions in reverse order.

This document was last generated on Dec 14, 2010.